

SUITABLE FOR 102 mm BORE WELL

Model	Stage	Motor Rating		Q m ³ /hr →	0	4.2	5.6	7.5	10	11	12.1	13.3
		HP	kW	Q lpm →	0	70	93	125	167	183	202	222
				H m/ St →	7.2	5.95	5.5	4.9	4	3.5	2.7	1.8
4HR10	4	1.00	0.75	Head in m ↓	29	24	22	20	16	14	11	7
4HR10	5	1.50	1.10	2" 50 mm	36	30	28	25	20	18	14	9
4HR10	6	1.50	1.10		43	36	33	29	24	21	16	11
4HR10	7	2.00	1.50		50	42	39	34	28	25	19	13
4HR10	8	2.00	1.50		58	48	44	39	32	28	22	14
4HR10	9	3.00	2.20		65	54	50	44	36	32	24	16
4HR10	10	3.00	2.20		72	60	55	49	40	35	27	18
4HR10	11	3.00	2.20		79	65	61	54	44	39	30	20
4HR10	12	3.00	2.20		86	71	66	59	48	42	32	22
4HR10	13	4.00	3.00		94	77	72	64	52	46	35	23
4HR10	14	4.00	3.00		101	83	77	69	56	49	38	25
4HR10	15	4.00	3.00		108	89	83	74	60	53	41	27
4HR10	16	4.00	3.00		115	95	88	78	64	56	43	29
4HR10	17	5.00	3.70		122	101	94	83	68	60	46	31
4HR10	18	5.00	3.70		130	107	99	88	72	63	49	32
4HR10	19	5.00	3.70		137	113	105	93	76	67	51	34
4HR10	20	5.00	3.70		144	119	110	98	80	70	54	36
4HR10	21	5.50	4.00		151	125	116	103	84	74	57	38
4HR10	22	5.50	4.00		158	131	121	108	88	77	59	40
4HR10	23	6.00	4.50		166	137	127	113	92	81	62	41
4HR10	24	6.00	4.50		173	143	132	118	96	84	65	43
4HR10	25	7.50	5.50	180	149	138	123	100	88	68	45	
4HR10	26	7.50	5.50	187	155	143	127	104	91	70	47	
4HR10	27	7.50	5.50	194	161	149	132	108	95	73	49	
4HR10	28	7.50	5.50	202	167	154	137	112	98	76	50	
4HR10	29	7.50	5.50	209	173	160	142	116	102	78	52	
4HR10	30	7.50	5.50	216	179	165	147	120	105	81	54	
4HR10	31	10.00	7.50	223	184	171	152	124	109	84	56	
4HR10	32	10.00	7.50	230	190	176	157	128	112	86	58	
4HR10	33	10.00	7.50	238	196	182	162	132	116	89	59	
4HR10	34	10.00	7.50	245	202	187	167	136	119	92	61	
4HR10	35	10.00	7.50	252	208	193	172	140	123	95	63	
4HR10	36	10.00	7.50	259	214	198	176	144	126	97	65	
4HR10	37	10.00	7.50	266	220	204	181	148	130	100	67	
4HR10	38	10.00	7.50	274	226	209	186	152	133	103	68	
4HR10	39	10.00	7.50	281	232	215	191	156	137	105	70	
4HR10	40	10.00	7.50	288	238	220	196	160	140	108	72	