

SUITABLE FOR 102 mm BORE WELL

Model	Stage	Motor Rating		Q m ³ /Hr →	0	1.7	2.3	3	4	4.4	4.8	5.3
		HP	kW	Q lpm →	0	28	38	50	67	73	80	88
				H m/ St →	7	6.2	5.85	5.35	4.5	4.05	3.25	2.25
4HR4	5	0.50	0.37	Head	35	31	29	27	23	20	16	11
4HR4	7	0.75	0.55	in	49	43	41	37	32	28	23	16
4HR4	8	0.75	0.55	m	56	50	47	43	36	32	26	18
4HR4	9	1.00	0.75	↓	63	56	53	48	41	36	29	20
4HR4	10	1.00	0.75		70	62	59	54	45	41	33	23
4HR4	13	1.50	1.10		91	81	76	70	59	53	42	29
4HR4	14	1.50	1.10	OUTLET	98	87	82	75	63	57	46	32
4HR4	15	1.50	1.10	inch	105	93	88	80	68	61	49	34
4HR4	17	2.00	1.50	mm	119	105	99	91	77	69	55	38
4HR4	18	2.00	1.50		126	112	105	96	81	73	59	41
4HR4	19	2.00	1.50		133	118	111	102	86	77	62	43
4HR4	20	2.00	1.50		140	124	117	107	90	81	65	45
4HR4	25	3.00	2.20	1½"	175	155	146	134	113	101	81	56
4HR4	26	3.00	2.20	32mm	182	161	152	139	117	105	85	59
4HR4	27	3.00	2.20		189	167	158	144	122	109	88	61
4HR4	28	3.00	2.20		196	174	164	150	126	113	91	63
4HR4	29	3.00	2.20		203	180	170	155	131	117	94	65
4HR4	30	3.00	2.20		210	186	176	161	135	122	98	68
4HR4	33	4.00	3.00		231	205	193	177	149	134	107	74
4HR4	34	4.00	3.00		238	211	199	182	153	138	111	77
4HR4	35	4.00	3.00		245	217	205	187	158	142	114	79
4HR4	36	4.00	3.00		252	223	211	193	162	146	117	81
4HR4	37	4.00	3.00		259	229	216	198	167	150	120	83
4HR4	38	5.00	3.70		266	236	222	203	171	154	124	86
4HR4	39	5.00	3.70		273	242	228	209	176	158	127	88
4HR4	40	5.00	3.70		280	248	234	214	180	162	130	90
4HR4	41	5.00	3.70		287	254	240	219	185	166	133	92
4HR4	42	5.00	3.70		294	260	246	225	189	170	137	95
4HR4	43	5.00	3.70		301	267	252	230	194	174	140	97
4HR4	44	5.00	3.70		308	273	257	235	198	178	143	99
4HR4	45	5.00	3.70		315	279	263	241	203	182	146	101
4HR4	46	5.00	3.70		322	285	269	246	207	186	150	104
4HR4	47	5.00	3.70		329	291	275	251	212	190	153	106
4HR4	48	5.00	3.70	OUTLET	336	298	281	257	216	194	156	108
4HR4	49	5.00	3.70	inch	343	304	287	262	221	198	159	110
4HR4	50	5.00	3.70	mm	350	310	293	268	225	203	163	113
4HR4	51	5.50	4.00		357	316	298	273	230	207	166	115
4HR4	52	5.50	4.00		364	322	304	278	234	211	169	117
4HR4	53	5.50	4.00		371	329	310	284	239	215	172	119
4HR4	54	5.50	4.00	1½"	378	335	316	289	243	219	176	122
4HR4	55	5.50	4.00	40 mm	385	341	322	294	248	223	179	124
4HR4	56	6.00	4.50		392	347	328	300	252	227	182	126
4HR4	57	6.00	4.50		399	353	333	305	257	231	185	128
4HR4	58	6.00	4.50		406	360	339	310	261	235	189	131
4HR4	59	6.00	4.50		413	366	345	316	266	239	192	133
4HR4	60	6.00	4.50		420	372	351	321	270	243	195	135
4HR4	61	7.50	5.50		427	378	357	326	275	247	198	137
4HR4	62	7.50	5.50		434	384	363	332	279	251	202	140
4HR4	63	7.50	5.50		441	391	369	337	284	255	205	142
4HR4	64	7.50	5.50		448	397	374	342	288	259	208	144
4HR4	65	7.50	5.50		455	403	380	348	293	263	211	146
4HR4	66	7.50	5.50		462	409	386	353	297	267	215	149
4HR4	67	7.50	5.50		469	415	392	358	302	271	218	151
4HR4	68	7.50	5.50		476	422	398	364	306	275	221	153
4HR4	69	7.50	5.50		483	428	404	369	311	279	224	155
4HR4	70	7.50	5.50		490	434	410	375	315	284	228	158